



MATTING FOR GENERAL USE

DESCRIPTION :

Z MATIZANTE USOS GENERALES is a filler of silica-based hydrated aluminum highly efficient matting.

CHARACTERISTICS:

Matting is a general purpose charge as it is suitable to refine economic or industrial use only for solvent-based products, achieving a decrease in brightness with an economic burden having the balance between quality and brightness cost.

USES:

Product recommended to get a decrease or reduction shine fast and easy way of economic products solvent base such as alkynd enamels, epoxies, etc.

RECOMENDED SYSTEM:

Add the appropriate dosage directly to the product.

COLORS:

Fine white powder.

TECHNICAL SPECIFICATIONS:

Density: 2.6000 g/cm³
Viscosity: Not applicable
Solids by Weight: Not applicable
Solids by Volumen: Not applicable
V O C: Not applicable

Theoretical Coverage:

Not applicable *** see observations

Recomended Dry Thickness:

Not applicable

PHYSICAL PROPERTIES:**Resistance To :**

Light: Not Applicable
Corrosion: Not Applicable
Abrasion: Not Applicable
Temperature: 95 °F

Flexibility: Not applicable
Adherence: NOT APPLICABLE
Hardness: NOT APPLICABLE
Shine: ***see observations

CHEMICAL PROPERTIES

Acids: Not Applicable
Alcalies: Not Applicable
Thinners: Not Applicable
Water: Not Applicable
Gasoline: Not Applicable

DRY:

Dust Free: Not applicable
Tact: Not applicable
Hard: Not applicable
To Repaint: Not applicable
For Inmersion: Not applicable

PRESENTATION:

1,00 Liters

APPLICATION:**Method:**

Conventional spray, brush or roller.

Thinner:

Solvent S-124 maximum 50%

Substrates :**SURFACE PREPARATION:**

Follow the instructions on the preparation of surface is in the application manuals and datasheets of finished once added the Z MATIZANTE USOS GENERALES.

**** DOSAGE ****

These doses are indicative and obtained from epoxy Solvent-based two components. It is generally recommended performing a test using two-thirds of the indicated dose and in no case exceed 50% by weight of the total base.

50% by weight of the base volume = less than 10 UDB.

25% of the total weight of base: 40-60 UDB

UDB determined at 60° angle.

STORAGING:

Preserved in original container tightly closed and stored in a cool, dry well ventilated

12 months

APPLICATION CONDITIONS:

Do not use this product if the ambient temperature is below 41°F (5°C). Do not apply the matting product if the substrate temperature is above 95°F (35°C) or 35.59 - 37.39°F (2-3°C) above the dew point, but not more than 95°F (35°C). APPLY THE PRODUCT AT NO DIRECT EXPOSURE TO SUNLIGHT.

Clean the equipment after finishing applying then product.

RECOMENDED TOP COATS

DUREPOXY® ER-B

OBSERVATIONS:

Ambient temperature above 41°F (5°C) less than 95°F (35°C). Substrate temperature: 2 to 3° C above the point of dew and less than 35° C. DO NOT APPLY paint on supports overheated by sun exposure, as this would cause a very fast evaporation of the solvent causing stained and overspray. Brightness level will decrease to the extent that increase the amount of additive. Are recommended in first, the same finish but bright tone and finish with one or two coats of tinted product, this last layer or layers applied until the opacity desired, will have to give a flash time between coats 10 to 15 minutes, DO NOT APPLY hands and heavily loaded clarified that the effect will not be achieved. Recommended use solvent S-124 for the application. THE EFFECT MAY VARY COLOR, THICKNESS FILM, SOLVENT USED, TECHNIQUE APPLICATION AND APPLICATION EQUIPMENT.

CAUTION:

This product will have to be applied in well ventilated areas and with adequate safety equipment, such as mask with double activate coal filter, goggles, cotton clothes and gloves, since it contains substances which extended inhalation can affect your health.

Consult with our technician before applying.

ATENION:

These suggestions and data are based on updated information and they are offered in good faith but without guarantee in what is concerning to the application of the product since the condition and methods of application are out of our control. Before the definitive utilization of the product, we recommend user to accomplish a detailed evaluation of the product, the sample will be provided to you by the Company.

Z96-49-MAUG- - -

Last Updated : 19/05/2014